

FAST - SOLVENT-FREE - READY TO USE

Fields of application:

- Strengthening of powdery and non compact surfaces
- Balance absorbency of too porous subfloors
- Impregnating heated subfloors with residual moisture content till 3CM%
- Impregnating the wet cement subfloors with residual moisture content till 4CM%
- Renovating the old parguet surface without parguet removing



Up to 50% lower spreading quantity comparing with solvent primers

After using primer PARKETOLIT PR51, adhesives PARKETOLIT 1549. PARKETOLIT 1550, PARKETOLIT E60 or PARKETOLIT E65 can be used.

Benefits of using primer PARKETOLIT PR51:

- 100% active substance.
- Odour less, solvent-free.
- **Ready to use**, one component, without diluting.
- Up to 50% lower consumption; only one coat to strengthen the surface and two coats to impregnate the wet cement subfloors are sufficient.
- Fast hardening primer allows flooring installation already 45 to 90 minutes after coating, and laying of parquet on wet screed already in one day.
- Without material waste, due to mixing too much product.

Packing:

•

Plastic vessels of 5L:

- For strengthen of powdery and porous surfaces: For impregnate the wet cement floors till 4CM%:
- $25 70 \text{ m}^2 (70 200 \text{ mL/m}^2)$ 18 - 35 m² (140 - 270 mL/m²)



Benefits of using primer:

Before laying floor coverings, the cement surface should be coated with primer in order to:

• Improve hardness of powdery and non compact subfloor





Balance absorbency of too porous subfloors





• Improve the glue adhesion to surface





• Allow the laying of parquet on cement screeds with increasing moisture content till 4CM% and save the time needed for laying wooden floors





For more information, please call ++386 573 12 326 or mail to prodaja@mitol.si.

