

MEKOL CREATIVE

dispersion adhesive for gluing of wood, paper and textile

| DESCRIPTION | MEKOL CREATIVE is water dispersed, solvent free adhesive for gluing wood, paper, textile and other materials. | |
|-----------------------------------|---|----------------------------------|
| FIELDS OF APPLICATION | For gluing, repairing and creating: AT SCHOOLS AND IN KINDERGARTENS: creative gluing of paper, carton, wood, textile, leather, artificial leather, cork on metal, stone, clay, gypsum, glass, insulation materials and plastic materials, AT HOME: gluing of paper, carton and various furniture repairs IN OFFICE: gluing of paper, cardboard and carton | |
| CHARACTERISTICS | solvent free adhesive the adhesive film is transparent the bond is strong and elastic cleaning of still fresh adhesive is possible by water | |
| DANGEROUS GOODS CLASSIFICATION | The product is not classified as dangerous. | |
| APPLICATION | The surfaces to be bonded must be straight, smooth, dry and free from dust, grease or other dirtiness. The adhesive can be spread in thin layer manually through the lengthening-piece on one of the surfaces. Surfaces should be pressed until the adhesive is still fresh. The pressing time depends on temperature, spread quantity, type, porosity and moisture content of glued material. Higher temperatures shorten the pressing time in the contrary the lower extends it. | |
| | The most convenient working conditions: Temperature of room and all materials involved Relative air humidity Moisture of wood | 18 - 23°C 65 - 75% 8 - 12% |
| PACKING | Available in 115g bottles with nozzle. | |
| STORAGE | Keep the product sealed in its original container at a temperature between +5°C and +25°C. PROTECT FROM FREEZE! The shelf life of the correctly stored product is 24 months. | |

The information provided herein, especially recommendations for the usage and application of our products, is based on our knowledge, results of laboratory tests and practical experience gained to date.

We guarantee a constant quality of our products under our technical specifications. Technical advice of our application department is available without obligation. This does not release the buyer from testing our products in his own responsibility with respect to their suitability for intended application and application process. Such an evaluation should be repeated if materials are changed in any way or bought from a different source.

We do not accept any liability with regard to above information or with regard to any verbal recommendation since different materials used in conjunction with our products as well as varying working conditions are beyond our control.